

UC-SB1-CAM-FLEX

UC Video Conference Smart Soundbar & Camera



- *A complete conferencing speakerphone and camera solution in one stunning front-of-room device*
- *Sleek and stylish soundbar design installs cleanly beneath the room display(s) — mounts on the wall or sits on a credenza*
- *Multicolor status bar — indicates audio volume, mute, and operational status*
- *180° far-field adaptive beamforming microphone array — senses who is speaking and optimizes directionality for clear pickup*
- *High-powered 2-way stereo speakers produce full, rich, and natural sound quality*
- *Advanced AEC & DSP technology — affords exceptional full-duplex audio performance with highly-intelligible, echo-free 2-way voice quality*
- *Built-in Huddly IQ™ camera — a premium conferencing camera fully integrated into the soundbar*
- *Ultra wide-angle 150° diagonal field of view — captures the entire room*
- *Genius Framing lossless digital autozoom — automatically detects people and frames them perfectly in the shot¹*
- *Full HD 1080p video resolution, precision optics, and advanced video processing — delivers a crystal clear video image*
- *3x digital zoom, pan, and tilt — allows manual shot control*
- *People counting — enables room usage analytics via Crestron XiO Cloud™ service when used with the UC-ENGINE or UC-ENGINE-SD*
- *USB 3.0 — provides audio and video connectivity through a single USB interface*
- *Plug & Play — compatible with major computer OS platforms running any web conferencing software*
- *Analog audio I/O — input and output connections for local source and assistive listening devices*
- *Integral hinged mounting bracket — simplifies wall mount installation*
- *Internal power supply — 100 to 240 VAC line powered*

An incredible front-of-room device, the Crestron® UC Video Conference Smart Soundbar & Camera (UC-SB1-CAM-FLEX) eliminates the need to install additional microphones, speakers, or cameras. Mounted on the wall or placed on a credenza beneath the main room display(s), the smart soundbar looks great and sounds even better in any small to medium-sized meeting space.

High-powered stereo speakers, adaptive beamforming microphone, and advanced digital signal processing deliver exceptional full-duplex speakerphone performance with highly intelligible, echo-free voice clarity. A perfect view of the room is achieved through the built-in conferencing camera featuring HD 1080p video resolution, ultra-wide 150° diagonal field of view, and Genius Framing digital autozoom.¹ Its compact design reduces clutter on the conference table, and even accommodates rooms with no table at all.

NOTE: See also model UC-SB1-FLEX for a similar solution with no built-in camera. The UC-SB1-FLEX allows for the use of any USB camera mounted separately from the smart soundbar.

USB Speakerphone & Camera

The UC-SB1-CAM-FLEX comprises a high-performance AEC-enabled speakerphone and camera. It is available as part of a complete [Crestron Flex](#) UC video conference system kit. A single USB 3.0 connection provides a plug-and-play interface to the Crestron UC-ENGINE as part of a Crestron Flex System.

Superb Sound Quality

The smart soundbar facilitates conversations with exceptional audio fidelity and pickup. Its integrated 180° far-field microphone array faithfully captures voices throughout the room using adaptive beamforming technology. Its high-powered, two-way stereo speakers produce full, rich and real sounding audio. High-performance AEC technology achieves transparent full-duplex performance free of distracting echo or noise. Additional digital signal processing assures optimal sound quality for an immersive experience.

UC-SB1-CAM-FLEX

UC Video Conference Smart Soundbar & Camera

Intelligent HD Camera

The integrated Huddly IQ™ camera features an ultra wide-angle 150° diagonal field of view to capture an entire conference room in Full HD 1080p video resolution. High precision aspherical optics, 12 MP CMOS sensor, and advanced video processing ensure an immersive, crystal clear video image free from light or noise artifacts or optical aberrations.

Genius Framing digital autozoom intelligently detects the people in the room and frames them perfectly for an optimal view. With Genius Framing, there's no need to control the camera manually or rely on stored presets. When conferencing, the camera image adjusts automatically to frame everyone in the shot.¹

Analog Audio Input & Output

Additional audio connectivity is provided through unbalanced stereo analog input and output jacks on the rear panel. The input accommodates any line-level audio source, which simply feeds to the internal amplifier and speakers with no volume control or other signal processing. The output is provided to feed an assistive listening system, and carries the same audio signal as the soundbar speakers.

Easy Installation

Installation is a breeze using the integral hinged mounting bracket, which attaches easily to the wall and allows the soundbar to be tipped forward for full access to the rear panel connections. Once installed and connected, the soundbar is held upright magnetically for normal operation. The bracket allows for attachment to any wall surface using two screws. A total of eight mounting keyholes, arranged in 2 in. (51 mm) increments, accommodates any wall stud spacing from 12 to 24 in. (305 to 610 mm). Alternately, the soundbar can be simply placed on a shelf or credenza. Optimal results are achieved by positioning the unit at ear/face height. A single 100-240 VAC outlet is required to power the unit.

Specifications

Speakers

Woofers: (2) 3 in. (76 mm) polypropylene cone w/rubber surround

Passive Radiators: (2) 3 x 4-3/8 in. (76 x 112 mm) polypropylene cone w/rubber surround

Tweeters: (2) 1 in. (25 mm) polyester dome

Amplifier Power: 20 W RMS per channel, stereo

Frequency Response: 80 Hz to 20 kHz (±3 dB)

Effective Output Level: 91 dB SPL @ 1 m, both channels driven at full power

Microphone

Microphone: Linear quad-element far-field adaptive beamforming microphone array

Pickup Range: 15 ft. (4.6m)²

Pickup Angle: 180° Horizontal

Frequency Response: 20 Hz to 8 kHz

Audio

DSP: Acoustic echo cancellation, dereverberation, automatic gain control, dynamic noise suppression, adaptive beamforming, speaker volume control, speaker EQ and limiting (fixed); full-duplex IEEE 1329 Type 1 compliant;

NOTE: DSP affects USB audio in/out only unless noted otherwise

USB Audio In/Out: USB 3.0, UAC 1.0 & HID, AEC-enabled USB speakerphone, 2-channel stereo far-end/content signal input, 2-channel mono microphone signal output; plug & play compatible with Crestron UC-ENGINE

Analog Input: 2-Channel stereo, fixed level (bypasses DSP), for in-room amplification of an external audio source

Analog Input Sensitivity: 1 Vrms per channel for full rated output

Analog Output: 2-Channel stereo, fixed level, feeds amplified audio content to an assistive listening system;

NOTE: Output level varies for USB input signal only according to the speaker volume control setting; analog input signal passes through without volume control or DSP

UC-SB1-CAM-FLEX

UC Video Conference Smart Soundbar & Camera

Camera

Model: Huddly IQ (mounted internally)

Image Sensor: 12 megapixel Sony® IMX477 Type 1/2.3 CMOS sensor

Lens: High precision, ultra wide angle, six element aspherical glass lens

Field of View: 150° diagonal, 120° horizontal, 90° vertical

Aperture: f/2.8

Processor: Intel® Movidius® Myriad® X VPU with Neural Compute Engine hardware accelerator

Pan/Tilt/Zoom: 3x lossless digital zoom, pan, and tilt

Autozoom: Genius Framing automatic lossless digital zoom intelligently frames people in the room¹

Dynamic Light Optimization: Auto-adjusts light levels and white balance

Noise Reduction: 3D noise reduction, bias compensating spatio-temporal filtering, wide area chroma filtering, flicker elimination

Scaling: Real-time scaling, dewarping, and perspective correction

People Counting: Detects and reports the number of people in frame

Video

USB Video Out: USB 3.0, UVC 1.1 & HID, conferencing camera; plug & play compatible with Crestron UC-ENGINE

Output Resolution: HD 1080p @ 30 fps

Color Space: YCbCr 4:2:0, YCbCr 4:2:2, MJPEG

Indicators

Status Bar: (1) Multi-segment RGBY LED zero-center mutually-diverging linear bargraph; Indicates the speaker volume, microphone mute, and speaker mute in red and green LEDs

Connectors

AUDIO IN: (1) 3.5 mm TRS mini-phone jack; Unbalanced stereo line-level audio input; Input Level: 1 Vrms maximum; Input Impedance: 10k Ohms

AUDIO OUT: (1) 3.5 mm TRS mini-phone jack; Unbalanced stereo line-level audio output; Output Level: 1 Vrms maximum; Output Impedance: 100 Ohms

PC: (1) USB 3.0 Type-B connector, female; USB 3.0 device port; Connects to UC-ENGINE or computer; 6 ft (1.83 m) USB 3.0 Type B to Type A cable included

CAMERA: (1) USB 3.0 Type-A connector, female; USB 3.0 host port; Connects to the internal camera output via a 6 in. (13 cm) USB Type-C™ to USB 3.0 Type A cable

100-240V~ 0.5A 50/60Hz: (1) IEC 60320 C14 main power inlet; Mates with removable power cord, included

Power

Main Power: 500 mA maximum @ 100-240 VAC, 50/60 Hz

Power Consumption: 22 W

Environmental

Temperature: 41° to 104° F (5° to 40° C)

Humidity: 10% to 90% RH (non-condensing)

Heat Dissipation: 75 BTU/hr

Construction

Enclosure: Lightly textured gunmetal black finish, plastic housing, perforated stainless steel grilles, die-cast aluminum rear cover, integral steel hinged mounting bracket

Mounting: Freestanding or surface wall mount at ear/face level (adhesive feet included, mounting bracket attached)

Dimensions

Height: 4.57 in. (117 mm), 4.64 in. (118 mm) with feet

Width: 43.60 in. (1108 mm)

Depth: 3.90 in. (100 mm)

Weight

Approximately 15 lb (6.8 kg)

Compliance

CE, IC, UL 62368-1, CSA C22.2 62368-1, EN 62368-1, IEC 62368-1, FCC Part 15 Class B, ICES-003 Issue 5 Class B, EN55022:2010 Class B, AS/NZS CISPR22:2010 Class B, AS/NZS CISPR 22:2010 Class B, EN55024:2010, EN61000-3-2:2014, EN61000-3-3:2013, RoHS compliant

UC-SB1-CAM-FLEX

UC Video Conference Smart Soundbar & Camera

Models & Accessories

Available Models

UC-SB1-CAM-FLEX

UC Video Conference Smart Soundbar & Camera

Available Accessories

CBL-AUDIO Series

Mini-TRS Stereo Audio Interface Cables

Notes:

1. Genius Framing is controlled by software via the UC-ENGINE when running Microsoft Teams™ Rooms.
2. Microphone pickup range may vary in rooms with highly reflective infrastructure (e.g., glass walls, metal furniture, open ceilings, etc.) or above average ambient noise.

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/How-To-Buy/Find-a-Representative or by calling 855-263-8754.

Additional resources can be accessed via the Crestron Commercial Lighting Consultants Partner Portal at www.crestron.com/about/partner-info/commercial-lighting-consultants. For assistance with incorporating this product into a design or specification, please contact the Commercial Lighting Consultant Hotline via email at clcdesign@crestron.com or by calling 888-330-1502.

The specific patents that cover Crestron products are listed online at www.crestron.com/legal/patents.

Certain Crestron products contain open source software. For specific information, visit www.crestron.com/opensource.

Crestron and the Crestron logo are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Huddly IQ is either a trademark or registered trademark of Huddly AS in the United States and/or other countries. Intel is either a trademark or registered trademark of Intel Corporation in the United States and/or other countries. Huddly is either a trademark or registered trademark of Kubicam AS in the United States and/or other countries. Microsoft Teams is either a trademark or registered trademark of Microsoft Corporation in the United States and/or other countries. Movidius and Myriad are either trademarks or registered trademarks of Movidius Ltd in the United States and/or other countries. Sony is either a trademark or registered trademark of Sony Corporation in the United States and/or other countries. USB Type-C is either a trademark or registered trademark of USB Implementers Forum, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography.

Specifications are subject to change without notice.

©2020 Crestron Electronics, Inc.

UC-SB1-CAM-FLEX

UC Video Conference Smart Soundbar & Camera

